

TOP GUN

IGNITION LEAD SPECIALISTS



TOP GUN - SUPPRESSION CABLE - 7mm and 8mm Double insulated, high temperature silicone cable (250°C plus). Features a reinforced fibreglass braid interwoven between the layers of silicone insulation. The conductor utilises a conductive silicone core impregnated with conductive graphite rovings. This conductor has excellent RFI suppression qualities, with a resistance of approximately 10,000Ω per metre length.



TOP GUN MAX 300 HEAVY DUTY - 5mm, 7mm and 8mm Premium quality cable, double insulated, high temperature silicone cable, rated 300°C plus (peak operating). Features a reinforced fibreglass braid interwoven between the layers of insulation. A patented formulation is applied over the jacket which chemically grafts to the jacket material. The grafted surface enhances the abrasion and heat resistance of the finished conductor. The conductor utilises a spirally wound stainless steel construction, in which stainless steel wire is helically wound around either a ferrite or kevlar carrier. This conductor has excellent RFI suppression qualities, with a resistance less than 1,000Ω per metre length. This cable is uniquely suited for situations where the original cable holders are to be used. The cable allows a premium spark, and is especially suited for all LP Gas applications. Kits are only available in Black, and are made of the same cable diameter as original sets where applicable.



TOP GUN - PRO RACING SPIRAL WIRE - 8.8mm and 10.0mm Double insulated, high temperature cable (250°C plus). Features a reinforced fibreglass braid interwoven between the layers of silicone insulation. The conductor utilises a spirally wound stainless steel construction, in which a single stainless steel wire is helically wound around either a ferrite or kevlar carrier. This conductor has good RFI suppression qualities, with a resistance of between 2,000-2,700Ω per metre length. Uniquely suited for performance applications, for both race track and street applications. Please refer to performance wires as detailed under the "Products" section of this website



TOP GUN - PRO RACING UNSUPPRESSED WIRE CORE CABLE - 8mm and 10.0mm Double insulated, high temperature cable (250°C plus). Features a reinforced fibreglass braid interwoven between the layers of silicone insulation. The conductor is nickel coated copper, with almost zero resistance. This product provides the maximum possible spark. Ideal for the Hi-Performance Race Track situation where RFI interference suppression is not important. **Not suitable for street or computerised ignition applications.**